

Anti-Graffiti Removal & Prevention Products Estimated Coverage Data



Graffiti Removal Options for an EnduraGuard Treated Surface*

- ❖ GraffitiClean gel and water rinse
- ❖ Wipe surface with a towel after GraffitiClean gel is applied
- ❖ Pressure washing with water under 1000 psi – (Over 1000 psi may damage coating)
- ❖ Water and detergent at no more than 10% concentration
- ❖ Mineral Spirits and Towel (or acetone cleaner)
- ❖ Any light alkaline or citrus cleaners.

*Always test cleaners in a small inconspicuous area prior to application

GraffitiClean Gel General Use

- ❖ **GraffitiClean Gel** will clean 1,000 - 1,600 square feet per 32 ounce bottle (depending on substrate)



EnduraGuard 41 Coverage Data

COVERAGE RATES**	
Surface	Sq. Ft. per gallon
Exterior Brick	300-550
Concrete	300-600
Concrete Block	300-550
Stucco	350-500
Smooth Stone	400-600
Bridges	400-600
Rough Wood	500-600
Smooth Wood	500-650
Wood Shingles	350-450
Metal(s)	600-800
Smooth Painted	600-800
Rough Painted	500-650

**Coverage may vary depend on desired cleanability and longevity.

Consult Manufacturer at 844 MICROBE for any application questions.