



## SD Auto PLUS Application Instructions

- Product should be at 70° F or higher at time of application.
- Do not store below 60° F or allow product to freeze.
- SD Auto PLUS is applied utilizing a hand held sprayer @ 25 PSI that atomizes the SD Auto PLUS™ solution, enabling the technology to coat large amounts of surface area completely and efficiently. SD Auto PLUS should NOT be applied with an electrostatic spray device.
- SD Auto PLUS™ can be applied to fabric, vinyl and leather as well as to most hard surfaces.
- Test material for color fastness in an inconspicuous location prior to application. SD Auto PLUS is water based.
- SD Auto PLUS™ must be applied to surfaces that are free of dust, dirt and oils to allow it to adhere. Pre-clean all surfaces prior to application and allow to dry.
- Protect exterior vehicle surfaces if necessary.
- SD Auto PLUS™ should be wiped from windows with a lint free microfiber cloth once a light haze appears on the surface. We recommend rolling down all windows prior to spraying of product.
- Typical amount of SD Auto PLUS™ required to treat a typical vehicle interior: 6 Ounces
- Utilize appropriate respirator, safety glasses and protective clothing when applying SD Auto PLUS and other SD Labs' products.
- Comply with all applicable safety requirements. Dispose of unused product and product containers in accordance with local and federal requirements.
- Do not reuse product container
- Please contact SD Labs at 844 MICROBE with any questions.

SD Auto products are available through your Global Shield Solutions and SD Labs Representative.

[www.SDLabs.com](http://www.SDLabs.com)

Tel: +1 844 MICROBE (844 642-7623)